

Part Number
40C9611

Print Technology
Color Laser

Function
Color Copying
Color Faxing
Color Printing
Color Scanning
Color Network Scanning

Workgroup Size
Medium-Large Workgroup

Touch Screen Display
Yes

Display
Lexmark e-Task 7-inch (17.8 cm)
color touch screen

Print Speed (Letter, Black)
Up to 50 ppm⁶

Print Speed (Letter, Color)
Up to 50 ppm⁶

Print Speed (Letter, Black) Duplex
Up to 40 spm⁶

Time to First Page (Black)
As fast as 5.0 seconds

Time to First Page (Color)
As fast as 5.5 seconds

Duplex (2-sided) Printing
Integrated Duplex

Print Resolution, Black
1200 x 1200 dpi
4800 Color Quality (2400 x 600 dpi)

Print Resolution, Color
1200 x 1200 dpi
4800 Color Quality (2400 x 600 dpi)

Copy Speed (Letter, Black)
Up to 50 cpm⁶

Copy Speed (Letter, Color)
Up to 50 cpm⁶

Time to First Copy (Black)
As fast as 6.5 seconds

Time to First Copy (Color)
As fast as 7.0 seconds

Reduce / Enlarge Range
25 - 400 %

A4/Ltr Simplex Scan Speed (Black)
Up to 56 / 60 sides per minute

A4/Ltr Simplex Scan Speed (Color)
Up to 56 / 60 sides per minute

A4/Ltr Duplex Scan Speed (Black)
Up to 26 / 28 sides per minute

A4/Ltr Duplex Scan Speed (Color)
Up to 26 / 28 sides per minute

Scan Area, Maximum
8.5 x 14 inches

ADF Scan
RADF (Reversing Duplex)

Scanner Type
Flatbed scanner with ADF

Scan Technology
CCD

Optical Scanning Resolution
300 X 300 ppi (color)
600 X 600 ppi (black)

Scan File Formats (Send as)
JPEG, JPG
PDF
Secure PDF
TIFF
XPS
Archival PDF (A-1a, A-1b)
Searchable PDF (optional OCR with 1GB RAM and hard disk required)
Highly compressed PDF (1GB RAM and hard disk required)

Scan Destinations
e-mail
FTP
USB Flash drive
USB or Network connected computer
Lexmark Document Solutions Suite (LDSS)

Modem Speed
ITU T.30, V.34 Half-Duplex, 33.6 Kbps

Fax Transmission Speed
< 3 seconds per page

Processor Speed
Quad Core 1.2 GHz

Memory, Standard
2048 MB

Memory, Maximum
4096 MB

Hard Disk
Included in configuration

Apple Operating Systems Supported
Apple OS X (10.6, 10.7, 10.8, 10.9, 10.10, 10.11)

Citrix MetaFrame
Microsoft Windows Server 2008 and 2008 X64 Edition with Citrix XenApp 5.0
Microsoft Windows Server 2008 R2 with Citrix XenApp 6.0, 6.5
Microsoft Windows Server 2012 with Citrix XenApp 6.0, 6.5

Linux Operating Systems Supported
Debian GNU/Linux 7.0, 8.0
Fedora 21, 22
Linpus Linux Lite Desktop 2.1
Linux Mint 13 LTS, 17 LTS, 17.1 LTS, 17.2 LTS
Linux Mint 2 Debian
PCLinuxOS 2014.12
Red Hat Enterprise Linux WS 4, 5, 6, 7
SUSE Linux Enterprise Desktop 10, 11, 12
SUSE Linux Enterprise Server 10, 11, 12
Ubuntu 12.04 LTS, 14.04 LTS, 15.04
openSUSE 13.1, 13.2
openSUSE Tumbleweed

Microsoft Windows Operating Systems Supported
Windows XP
Windows XP x64
Windows Vista
Windows Vista x64
Windows Server 2008
Windows Server 2008 x64
Windows 7
Windows 7 x64
Windows Server 2008 R2
Windows 8
Windows 8 x64
Windows Server 2012
Windows 8.1
Windows 8.1 x64
Windows Server 2012 R2
Windows RT
Windows RT 8.1
Windows 10

Novell Operating Systems Supported
Novell NetWare 6.5 Open Enterprise Server
Novell Open Enterprise Server 2 on SUSE Linux Enterprise Server 10 SP4
Novell Open Enterprise Server 11 on SUSE Linux Enterprise Server 11

UNIX Operating Systems Supported
Sun Solaris x86 10, 11
Sun Solaris SPARC 10, 11
IBM AIX 6.1, 7.1

Included Paper Handling
550-Sheet Input
100-Sheet Multipurpose Feeder
Integrated Duplex
300-Sheet Output Bin

Optional Paper Handling
550-Sheet Tray

Paper Input Capacity, Standard
Up to 650 pages 20 lb or 75 gsm bond

Paper Input Capacity, Maximum
Up to 2300 pages 20 lb or 75 gsm bond

Paper Output Capacity, Standard
Up to 300 pages 20 lb or 75 gsm bond

Paper Output Capacity, Maximum
Up to 300 pages 20 lb or 75 gsm bond

Paper Weight Range Supported - Standard Tray (lb.)
16 - 58 lb.

Paper Weight Range Supported - Multipurpose Feeder (lb.)
16 - 58 lb.

Integrated Tray Card Stock Upper limit (grain long)
Index Bristol - 199 gsm (110 lb)
Tag - 163 gsm (100 lb)
Cover - 176 gsm (65 lb)

Integrated Tray Card Stock Upper limit (grain short)
Index Bristol - 199 gsm (110 lb)
Cover - 216 gsm (80 lb)
Tag - 203 gsm (125 lb)

ADF
50-Sheet Automatic Document Feeder

ADF Paper Input Capacity
Up to 50 pages 20 lb or 75 gsm bond

ADF Paper Output Capacity
Up to 50 pages 20 lb or 75 gsm bond

Finishing Option
No

Number of Paper Inputs, Standard
2

Number of Paper Inputs, Maximum
5

Media Types Supported
Card Stock
Envelopes
Paper Labels
Plain Paper
Vinyl Labels
Refer to the Card Stock & Label Guide.
Banner Paper

Media Sizes Supported

10 Envelope
 7 3/4 Envelope
 9 Envelope
 A4
 A5
 B5 Envelope
 C5 Envelope
 DL Envelope
 Executive
 Folio
 JIS-B5
 Legal
 Letter
 Statement
 Universal
 Oficio
 A6

Standard Ports

One Internal Card Slot
 USB 2.0 Specification Hi-Speed Certified (Type B)
 Gigabit Ethernet (10/100/1000)
 Front USB 2.0 Specification Hi-Speed Certified port (Type A)
 Rear Hi-Speed USB Port Compatible with USB 2.0 Specification (Type A)

Optional Network Ports

Internal MarkNet N8360
 802.11b/g/n Wireless, NFC

Direct USB

Yes

Ethernet Network

Yes

Wireless

Wireless Option

Network Protocol Support

TCP/IP IPv4
 TCP/IP IPv6
 TCP
 UDP

Network Printing Methods

LPR/LPD
 Direct IP (Port 9100)
 Enhanced IP (Port 9400)
 Secure IP (Port 96xx)
 FTP, TFTP
 Telnet
 IPP 1.0, 1.1, 2.0 (Internet Printing Protocol)
 Microsoft Web Services WSD
 Pull Printing

Network Management Protocols¹

HTTP
 HTTPs (SSL/TLS)
 SNMPv1, SNMPv2c
 SNMPv3
 WINS
 IGMP
 BOOTP, RARP
 APIPA (AutoIP)
 DHCP
 ICMP
 DNS
 Bonjour
 DDNS
 mDNS
 ARP
 NTP
 Telnet
 Finger

Network Security

SNMPv3
 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS
 IPsec

Printer Languages (Standard)

PCL 5c Emulation
 PCL 6 Emulation
 Personal Printer Data Stream (PPDS)
 PostScript 3 Emulation
 Direct Image
 Microsoft XPS (XML Paper Specification)
 AirPrint™
 PDF 1.7 emulation

Fonts and Symbol Sets

3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide
 2 PCL bitmap fonts
 39 scalable PPDS fonts
 84 scalable PCL fonts
 OCR-A, OCR-B scalable PCL 5e fonts
 For more information, refer to the Technical Reference.
 165 scalable PostScript fonts
 15 PPDS bitmap fonts

Laser Cartridge Yields (up to)⁵

20,000-page Black High Yield Cartridge
 13,000-page Color (CMY) High Yield Cartridges

Imaging Unit Estimated Yield

Up to 150000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage⁴

Cartridge(s) Shipping with Product

7,000-page Black and Color (CMYK) Return Program Toner Cartridges

Replacement Cartridges:

Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details.

Packaged Size (in. - H x W x D)

37.6 x 27.6 x 28.9 in.

Packaged Weight (lb.)

141.3 lb.

Size (in. - H x W x D)

25.5 x 19.9 x 21 in.

Weight (lb.)

99 lb.

Noise Level, Idle

16 dBA

Noise Level (Print), Operating

53 dBA

Duplex Print Noise Level, Operating

55 dBA

Noise Level (Copy), Operating

56 dBA

Noise Level (Scan), Operating

53 dBA

ENERGY STAR

Yes

Average Power (Hibernate Mode)

0.2 watts

Average Power (Sleep Mode)

2.6 watts

Average Power (Ready Mode)

100 watts

Average Power (Printing)

700 watts

Average Power (Copying)

460 watts

Average Power (Scanning)

85 watts

ENERGY STAR Typical Electricity Consumption (TEC)

2.4 kilowatt-hours per week

Limited Warranty - See Statement of Limited Warranty

1-Year Parts Only Service

Product Certifications

ENERGY STAR, ICES-003 Class B, BSMI Class B, VCCI Class B, FCC Class B, NOM-032, UL, cUL, NOM, US FDA/CDRH, IEC 60825-1, CB Report, ISO-532B, CE (EU) DoC, EFTA (CE), KC logo, CCC, C-tick DoC, EuP, CECP, CEL, EC 1275/2008, ECMA-370, TED, SII, TER, SABS, UL-AR, GS Mark, Green Dot, ISO-9296, COC, CCD-035 EcoLogo, Green Mark, EPEAT

Maximum Monthly Duty Cycle

Up to 150000 pages per month³

Recommended Monthly Page Volume

2000 - 20000 pages²

Specified Operating Environment

Humidity: 8 to 80% Relative Humidity

Temperature: 10 to 32°C (50 to 90°F)

Altitude: 0 - 2896 Meters (9,500 Feet)

License/Agreement Terms

Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details.

Country of Origin

China (PRC)

UNSPSC Code

43212110

Harmonized Tariff Code

8443.31.0000

¹This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (<http://www.openssl.org/>)

²"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

³"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.

⁴Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity.

⁵Average yield at approximately 5% print coverage per colour.

⁶Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.