

Lexmark C2240



| | |
|--|---|
| Part Number | 42C0008 |
| Print Technology | Color Laser |
| Workgroup Size | Small-Medium Workgroup |
| Touch Screen Display | Yes |
| Display | Lexmark e-Task 4.3-inch (10.9 cm) color touch screen |
| Print Speed (Letter, Black) | Up to 40 ppm ⁶ |
| Print Speed (Letter, Color) | Up to 40 ppm ⁶ |
| Print Speed (Letter, Black) Duplex | Up to 20 spm ⁶ |
| Print Speed (Letter, Color) Duplex | Up to 20 spm ⁶ |
| Time to First Page (Black) | As fast as < 7 seconds |
| Time to First Page (Color) | As fast as < 7 seconds |
| Duplex (2-sided) Printing | Integrated Duplex |
| Print Resolution, Black | 1200 x 1200 dpi |
| Print Resolution, Color | 4800 Color Quality (2400 x 600 dpi) |
| Processor | Dual Core, 1000 MHz |
| Memory, Standard | 1024 MB |
| Memory, Maximum | 1024 MB |
| Hard Disk | Option available |
| Apple Operating Systems Supported | Apple OS X (10.6, 10.7, 10.8, 10.9, 10.10, 10.11, 10.12) |
| Citrix MetaFrame | Microsoft Windows 2000 Server running Terminal Services with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0. |
| | Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 4.0 |
| | Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 3.0, 4.0 |
| | Microsoft Windows Server 2012 with Citrix XenApp 6.0, 6.5 |
| Linux Operating Systems Supported | Debian GNU/Linux 7.0, 8.0 |
| | SUSE Linux Enterprise Server 10, 11, 12 |
| | openSUSE 13.1, 13.2 |
| | Ubuntu 16.04 LTS |
| | Fedora 23, 24 |
| | Red Hat Enterprise Linux WS 6, 7 |
| | openSUSE Linux 42.3 |
| Microsoft Windows Operating Systems Supported | Windows 7 |
| | Windows 7 x64 |
| | Windows 8 |
| | Windows 8 x64 |
| | Windows 8.1 |
| | Windows 8.1 x64 |
| | Windows 10 |
| Novell Operating Systems Supported | Novell NetWare 6.5 Open Enterprise Server |
| | Novell NetWare 5.1(SP 6+), 6.0(SP 3+) with Novell Distributed Print Services (NDPS) |
| | Novell Open Enterprise Server on SUSE Linux Enterprise Server |
| | Novell Open Enterprise Server 2 on SUSE Linux Enterprise Server 10 SP4 |
| | Novell Open Enterprise Server 11 on SUSE Linux Enterprise Server 11 |
| | Novell Open Enterprise Server 2 SP2 on SuSE Linux Enterprise Server 10 SP3 3 |

| | |
|--|--|
| UNIX Operating Systems Supported | Sun Solaris x86 10, 11 |
| | Sun Solaris SPARC 10, 11 |
| | IBM AIX 6.1, 7.1 |
| Included Paper Handling | 250-Sheet Input |
| | 125-Sheet Output Bin |
| | Integrated Duplex |
| | Single-Sheet Manual Feed |
| Optional Paper Handling | 550-Sheet Tray |
| | 650-Sheet Duo Tray |
| Paper Input Capacity, Standard | Up to 250+1 pages 20 lb or 75 gsm bond |
| Paper Input Capacity, Maximum | Up to 1450+1 pages 20 lb or 75 gsm bond |
| Paper Output Capacity, Standard | Up to 125 pages 20 lb or 75 gsm bond |
| Paper Output Capacity, Maximum | Up to 125 pages 20 lb or 75 gsm bond |
| Paper Weight Range Supported - Standard Tray (lb.) | 24.1 - 28 lb. |
| Integrated Tray Card Stock Upper limit (grain long) | Cover - 200 gsm (74 lb) |
| | Index Bristol - 200 gsm (110 lb) |
| | Tag -200 gsm (122 lb) |
| Finishing Option | No |
| Number of Paper Inputs, Standard | 2 |
| Number of Paper Inputs, Maximum | 5 |
| Media Types Supported | Card Stock |
| | Envelopes |
| | Paper Labels |
| | Plain Paper |
| | Vinyl Labels |
| | Refer to the Card Stock & Label Guide. |
| Media Sizes Supported | 10 Envelope |
| | 7 3/4 Envelope |
| | 9 Envelope |
| | A4 |
| | A5 |
| | C5 Envelope |
| | DL Envelope |
| | Hagaki Card |
| | Executive |
| | Folio |
| | JIS-B5 |
| | Legal |
| | Letter |
| | Statement |
| | Universal |
| | Oficio |
| | A6 |
| Standard Ports | USB 2.0 Specification Hi-Speed Certified (Type B) |
| | Gigabit Ethernet (10/100/1000) |
| | Front USB 2.0 Specification Hi-Speed Certified port (Type A) |
| | Rear USB 2.0 Specification Hi-Speed Certified Port (Type A) |
| Optional Network Ports | Marknet N8372 WiFi Option |
| Direct USB | Yes |
| Ethernet Network | Yes |
| Network Protocol Support | TCP/IP IPv4 |
| | AppleTalk™ |
| | TCP/IP IPv6 |
| | TCP |
| | UDP |
| Network Printing Methods | LPR/LPD |
| | Direct IP (Port 9100) |
| | Enhanced IP (Port 9400) |
| | FTP, TFTP |
| | ThinPrint .print integration |
| | Telnet |
| | IPP 1.0, 1.1, 2.0 (Internet Printing Protocol) |

| | |
|---|--|
| Network Management Protocols1 | HTTP |
| | HTTPs (SSL/TLS) |
| | SNMPv1, SNMPv2c |
| | SNMPv3 |
| | WINS |
| | IGMP |
| | APIPA (AutoIP) |
| | DHCP |
| | ICMP |
| | DNS |
| | Bonjour |
| | DDNS |
| | mDNS |
| | ARP |
| | NTP |
| | Telnet |
| | Finger |
| Network Security | SNMPv3 |
| | 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS |
| | IPSec |
| Printable Area | 0.17 inches of the top, bottom, right and left edges (within) |
| Printer Languages (Standard) | PCL 5c Emulation |
| | PCL 6 Emulation |
| | Personal Printer Data Stream (PPDS) |
| | PostScript 3 Emulation |
| | Direct Image |
| | Microsoft XPS (XML Paper Specification) |
| | AirPrint™ |
| | PDF 1.7 emulation |
| Fonts and Symbol Sets | 3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide |
| | 158 scalable PostScript fonts |
| | 2 PCL bitmap fonts |
| | 39 scalable PPDS fonts |
| | 5 PPDS bitmap fonts |
| | 84 scalable PCL fonts |
| | OCR-A, OCR-B scalable PCL 5e fonts |
| | For more information, refer to the Technical Reference. |
| Laser Cartridge Yields (up to)⁵ | 6,000-page Color (CMY) Cartridges |
| | 9,000-page Black Cartridge |
| Photoconductor Estimated Yield | Up to 125,000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage ⁴ |
| Cartridge(s) Shipping with Product | 2,000-page color (CMY) Return Program Toner Cartridges |
| | 3,000-page Black Starter Return Program Toner Cartridge |
| Replacement Cartridges: | Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details. |
| Packaged Size (in. - H x W x D) | 15.8 x 19.5 x 23.4 in. |
| Packaged Weight (lb.) | 52.5 lb. |
| Size (in. - H x W x D) | 18.2 x 17.4 x 23.1 in. |
| Weight (lb.) | 60 lb. |
| Noise Level, Idle | Inaudible dBA |
| Noise Level (Print), Operating | 51 dBA |
| Duplex Print Noise Level, Operating | 53 dBA |
| ENERGY STAR | Yes |
| Average Power (Hibernate Mode) | 0.2 watts |
| Average Power (Sleep Mode) | 1.5 watts |
| Average Power (Ready Mode) | 37 watts |
| Average Power (Printing) | 570 watts |
| ENERGY STAR Typical Electricity Consumption (TEC) | 1.6 kilowatt-hours per week |
| Limited Warranty - See Statement of Limited Warranty | 1-Year Advanced Exchange, Next Business Day |
| Product Certifications | ENERGY STAR, Blue Angel RAL-UZ-171, ICES-003 Class B, BSMI Class B, VCCI Class B, US FDA, UL 60950-1, FCC Class B, cUL CAN/CSA-C22.2 60950-1, CB EN/IEC 60950-1, CB EN/IEC 60825-1, CE DoC (EN 62301 Class B, EN 62311, CE EN/IEC 60950-1, CE EN/IEC 60825-1, EN 61000-3, EN 55022 Class B, EN 55024, UL), EFTA (CE), KCC, CCC, CECF, CEL, C-tick DoC, UL-AR, KC mark, UL GS mark, UCRF, EC 1275 |

| | |
|--|--|
| Maximum Monthly Duty Cycle | Up to 100000 pages per month ³ |
| Recommended Monthly Page Volume | 1500 - 10000 pages ² |
| Specified Operating Environment | Humidity: 8 to 80% Relative Humidity |
| | Altitude: 0 - 3048 Meters (10,000 Feet) |
| | Temperature: 10 to 32°C (50 to 90°F) |
| License/Agreement Terms | Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details. |
| Country of Origin | China (PRC) |
| UNSPSC Code | 43212105 |
| Harmonized Tariff Code | 8443.32.1010 |

¹This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (<http://www.openssl.org/>)
²"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

³"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.

⁴Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity.

⁵Average yield at approximately 5% print coverage per colour.

⁶Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.