Lexmark XM9165



Part Number

26Z0204

Print Technology

Monochrome Laser

Function

Color Scanning

Copying

Faxing

Network Scanning

Printing

Workgroup Size

Display

Departmental Workgroup

Touch Screen Display

Yes

Print Speed (Letter, Black)

Lexmark e-Task 10-inch (25 cm) class color touch screen

Up to 65 ppm6

Print Speed (Letter, Black) Duplex

Up to 65 spm6

Time to First Page (Black)

As fast as < 5.2 seconds

Duplex (2-sided) Printing Integrated Duplex

Print Resolution, Black

1200 Image Quality

1200 x 1200 dpi

2400 Image Quality

600 x 600 dpi **Copy Speed (Letter, Black)**

Up to 65 cpm6

Copy Speed (Letter, Black) Duplex

Time to First Copy (Black)

Up to 65 spm6

As fast as 5.6 seconds

Reduce / Enlarge Range 25 - 400 %

A4/Ltr Simplex Scan Speed (Black)

Up to 80 sides per minute

A4/Ltr Simplex Scan Speed (Color)

Up to 80 sides per minute

A4/Ltr Duplex Scan Speed (Black) Up to 140 sides per minute

A4/Ltr Duplex Scan Speed (Color)

Up to 140 sides per minute

Scan Area, Maximum 11.69 x 17.0 inches

ADF Scan

DADF (single pass Duplex) **Scanner Type**

Flatbed scanner with ADF

Scan Technology

CIS / CCD Hybrid

Optical Scanning Resolution

600 X 600 ppi (black)

up to 600 X 600 ppi (color)

Scan File Formats (Send as) JPEG, JPG

PDF

Secure PDF TIFF

XPS

Archival PDF (A-1a, A-1b)

Searchable PDF (optional OCR with 1GB RAM and hard disk required)

Highly compressed PDF (1GB RAM and hard disk required) **Scan Destinations**

e-mail

FTP USB Flash drive

USB or Network connected computer

Lexmark Document Solutions Suite (LDSS)

Modem Speed

ITU T.30, V.34 Half-Duplex, 33.6 Kbps

Fax Transmission Speed < 3 seconds per page

Processor

Dual Core, 800 MHz

1024 MB

Memory, Standard

y, Maximum	
3072 MB	

Hard Disk

Memor

Included in configuration

Apple Operating Systems Supported

Apple OS X (10.6, 10.7, 10.8, 10.9, 10.10)

Citrix MetaFrame

Microsoft Windows Server 2003 running Terminal Services with Citrix Presentation Server 3.0, 4.0, 4.5

Microsoft Windows Server 2003 x64 running Terminal Services

with Citrix Presentation Server 4.0 x64, 4.5 x64 Microsoft Windows Server 2003 and 2003 X64 Edition with Citrix

XenApp 5.0 Microsoft Windows Server 2008 and 2008 X64 Edition with Citrix

Microsoft Windows Server 2008 R2 with Citrix XenApp 6.0, 6.5

Linux Operating Systems Supported

XenApp 5.0

SUSE Linux Enterprise Server 10, 11

SUSE Linux Enterprise Desktop 10, 11

Red Flag Linux Desktop 6.0 Linpus Linux Desktop 9.6

Debian GNU/Linux 5.0, 6.0

Red Hat Enterprise Linux WS 4.0, 5.0, 6.0

PCLinuxOS 2011

Mint 10, 11, 12, 13

openSUSE 11.4, 12.1, 12.2 Ubuntu 12.04, 12.10

Fedora 17, 18, 19

Microsoft Windows Operating Systems Supported

Windows XP Windows Server 2003

Windows XP x64 Windows Server 2003 x64

Windows Vista

Windows Vista x64

Windows Server 2008 Windows Server 2008 x64

Windows 7

Windows 7 x64

Windows Server 2008 R2

Windows 8 Windows 8 x64

Windows Server 2012

Windows 8.1

Windows 8.1 x64 Windows Server 2012 R2

Windows RT

Novell Operating Systems Supported

Windows RT 8.1

Novell NetWare 6.5 Open Enterprise Server

Novell NetWare 5.1(SP 6+), 6.0(SP 3+) with Novell Distributed Print Services (NDPS)

Novell Open Enterprise Server on SUSE Linux Enterprise Server

UNIX Operating Systems Supported

HP-UX 11.11, 11.23, 11.31

Sun Solaris SPARC 9, 10, 11

Sun Solaris x86 10, 11 IBM AIX 5.3, 6.1, 7.1

Included Paper Handling

250-Sheet Output Bin

150-Sheet Multipurpose Feeder

2 x 500-Sheet Input

Optional Paper Handling

Staple Punch Finisher

2500-Sheet Tandem Tray 3000-Sheet Tray

Booklet Finisher

2 x 500-Sheet Trav

Paper Input Capacity, Standard

Up to 1150 pages 20 lb or 75 gsm bond Paper Input Capacity, Maximum

Up to 6650 pages 20 lb or 75 gsm bond

Paper Output Capacity, Standard

Paper Output Capacity, Maximum

Up to 3500 pages 20 lb or 75 gsm bond

Up to 250 pages 20 lb or 75 gsm bond

Paper Weight Range Supported - Standard Tray (lb.) 16 - 68 lb.

Paper Weight Range Supported - Multipurpose Feeder (lb.)

A3 / 11 x 17 Yes

ADF

100-Sheet Automatic Document Feeder **ADF Paper Input Capacity**

Up to 100 pages 20 lb or 75 gsm bond

Up to 100 pages 20 lb or 75 gsm bond

16 - 68 lb.

ADF Paper Output Capacity

Finishing Option Yes

Finishing Functions

Offset stacking

Stapling Hole punching

Booklet fold and saddle stapling

Number of Paper Inputs, Standard

Number of Paper Inputs, Maximum

Media Types Supported

Card Stock Envelopes

Labels Plain Paper

Transparencies Refer to the Card Stock & Label Guide.

Media Sizes Supported

10 Envelope 7 3/4 Envelope

9 Envelope А3

A4

A5 B5 Envelope

C5 Envelope DL Envelope

Folio JIS-B4

Executive

JIS-B5 Ledger Legal

Letter Statement

Super Tabloid (12 x 18") Oficio

Universal

SRA3 **Standard Ports**

A6

USB 2.0 Specification Hi-Speed Certified (Type B)

Gigabit Ethernet (10/100/1000)

One Internal Card Slot

Front USB 2.0 Specification Hi-Speed Certified port (Type A) Two Rear USB 2.0 Specification Hi-Speed Certified ports (Type A)

Internal RS-232C serial Internal 1284-B Bidirectional Parallel

Optional Network Ports

Internal MarkNet N8350 802.11b/g/n Wireless **Direct USB**

Yes

Optional Local Ports

Ethernet Network Yes

Network Protocol Support

TCP/IP IPv4 AppleTalk™

TCP/IP IPv6

TCP **UDP**

Network Printing Methods

LPR/LPD Direct IP (Port 9100)

Enhanced IP (Port 9400)

Secure IP (Port 96xx) FTP, TFTP

ThinPrint .print integration

Telnet

IPP 1.0, 1.1, 2.0 (Internet Printing Protocol) Microsoft Web Services WSD

Pull Printing **Network Management Protocols1**

> HTTPs (SSL/TLS) SNMPv1, SNMPv2c

> > SNMPv3

HTTP

IGMP BOOTP, RARP

WINS

APIPA (AutoIP) DHCP **ICMP**

DDNS mDNS

ARP

DNS

NTP Telnet

Finger

39 scalable PPDS fonts 5 PPDS bitmap fonts

OCR-A, OCR-B scalable PCL 5e fonts

25,000-page High Yield Cartridge

Photoconductor Estimated Yield Up to 125000 pages, based on 3 average letter/A4-size pages per

Cartridge(s) Shipping with Product

21,000-page Starter Toner Cartridge Packaged Size (in. - H x W x D)

Packaged Weight (lb.)

246 lb. Size (in. - $H \times W \times D$)

209.4 lb.

35.8 x 24.2 x 27.4 in.

Size, Trays Extended (in. - H x W x D) 51.44 x 37.5 x 49.07 in.

31 dBA

Noise Level (Print), Operating

56 dBA

55 dBA

Noise Level (Scan), Operating 56 dBA

Yes

0.6 watts

Average Power (Ready Mode) 220 watts

Average Power (Copying)

1000 watts **Average Power (Scanning)**

4.9 kilowatt-hours per week

Limited Warranty - See Statement of Limited Warranty 1-Year Parts Only

ENERGY STAR, ICES-003 Class A, BSMI Class A, VCCI Class A,

Product Certifications

GOST-R, SII, TER, Bel GISS, SABS, TUV-AR, KC mark, BIS, TUV-GS Mark

Altitude: 0 - 2500 Meters (8,200 Feet)

Temperature: 10 to 30°C (50 to 86°F)

Country of Origin

43212110

FCC Class A, NOM-032, cTUV, US FDA/CDRH, cTUVus, IEC 60825-1, CB Report, NCC Mark, FCC, CE (EU) DoC, EFTA (CE)

KCC, RCM, CCC, C-tick DoC, EuP, CECP, CEL, ECMA-370, TED,

Recommended Monthly Page Volume

15000 - 50000 pages2

Humidity: 15 to 85% Relative Humidity

8443.31.0000

Printable Area

(within)

Printer Languages (Standard) PCL 5e Emulation

Network Security

PCL 6 Emulation

Personal Printer Data Stream (PPDS) PostScript 3 Emulation

xHTML Direct Image

Microsoft XPS (XML Paper Specification)

AirPrint™ PDF 1.7 emulation

Fonts and Symbol Sets 3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide

158 scalable PostScript fonts 2 PCL bitmap fonts

84 scalable PCL fonts

For more information, refer to the Technical Reference Laser Cartridge Yields (up to)5

print job and ~ 5% coverage4

47 x 30 x 33 in.

Weight (lb.)

Noise Level, Idle

55 dBA **Duplex Print Noise Level, Operating**

Noise Level (Copy), Operating

ENERGY STAR

Average Power (Hibernate Mode)

Average Power (Sleep Mode) 3.6 watts

Average Power (Printing) 985 watts

230 watts **ENERGY STAR Typical Electricity Consumption (TEC)**

Maximum Monthly Duty Cycle Up to 300000 pages per month3

Specified Operating Environment

China (PRC) **UNSPSC Code**

Harmonized Tariff Code

SNMPv3 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS,

TTLS

0.167, .12, .12 inches of the top, bottom, right and left edges

IPSec

¹This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (http://www.openssl.org/)

²"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

³"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.

⁴Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity.

⁵Average yield based on approximately 5% print coverage.

⁶Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.