

Lexmark XM7370



Part Number	25B1204
Print Technology	Monochrome Laser
Function	Color Scanning Copying Faxing Network Scanning Printing
Workgroup Size	Large Workgroup
Touch Screen Display	Yes
Display	Lexmark e-Task 10-inch (25 cm) class color touch screen
Print Speed (Letter, Black)	Up to 70 ppm ⁶
Print Speed (Letter, Black) Duplex	Up to 42 spm ⁶
Time to First Page (Black)	As fast as 4.0 seconds
Duplex (2-sided) Printing	Integrated Duplex
Print Resolution, Black	1200 Image Quality 1200 x 1200 dpi 2400 Image Quality 300 x 300 dpi 600 x 600 dpi
Copy Speed (Letter, Black)	Up to 70 cpm ⁶
Copy Speed (Letter, Black) Duplex	Up to 44 spm ⁶
Time to First Copy (Black)	As fast as 4.0 seconds
Reduce / Enlarge Range	25 - 400 %
A4/Ltr Simplex Scan Speed (Black)	Up to 72 / 75 sides per minute
A4/Ltr Simplex Scan Speed (Color)	Up to 72 / 75 sides per minute
A4/Ltr Duplex Scan Speed (Black)	Up to 144 / 150 sides per minute
A4/Ltr Duplex Scan Speed (Color)	Up to 144 / 150 sides per minute
Scan Area, Maximum	8.5 x 14.0 inches
ADF Scan	DADF (single pass Duplex)
Scanner Type	Flatbed scanner with ADF
Scan Technology	CCD
Optical Scanning Resolution	600 X 600 ppi (black) up to 600 X 600 ppi (color)
Scan File Formats (Send as)	JPEG, JPG PDF Secure PDF TIFF XPS Archival PDF (A-1a, A-1b) Searchable PDF
Scan Destinations	e-mail FTP USB Flash drive USB or Network connected computer Lexmark Document Solutions Suite (LDSS)
Modem Speed	Max is 33,600 bps, V.34 Half-Duplex Kbps
Fax Transmission Speed	< 3 seconds per page
Processor	Quad Core, 1200 MHz
Memory, Standard	2048 MB

Memory, Maximum	6144 MB
Hard Disk	Included in configuration
Apple Operating Systems Supported	Apple OS X (10.6, 10.7, 10.8, 10.9, 10.10, 10.11, 10.12)
Citrix MetaFrame	Microsoft Windows 2000 Server running Terminal Services with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0. Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 4.0 Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 3.0, 4.0 Microsoft Windows Server 2012 with Citrix XenApp 6.0, 6.5
Linux Operating Systems Supported	Debian GNU/Linux 7.0, 8.0 SUSE Linux Enterprise Server 10, 11, 12 openSUSE Linux 13.2 Ubuntu 16.04 LTS Fedora 23, 24 Red Hat Enterprise Linux WS 6, 7 openSUSE Linux 42.3
Microsoft Windows Operating Systems Supported	Windows 7 Windows 7 x64 Windows 8 Windows 8 x64 Windows 8.1 Windows 8.1 x64 Windows 10
Novell Operating Systems Supported	Novell NetWare 6.5 Open Enterprise Server Novell NetWare 5.1(SP 6+), 6.0(SP 3+) with Novell Distributed Print Services (NDPS) Novell Open Enterprise Server on SUSE Linux Enterprise Server Novell Open Enterprise Server 2 on SUSE Linux Enterprise Server 10 SP4 Novell Open Enterprise Server 11 on SUSE Linux Enterprise Server 11 Novell Open Enterprise Server 2 SP2 on SuSE Linux Enterprise Server 10 SP3 3
UNIX Operating Systems Supported	Sun Solaris x86 10, 11 Sun Solaris SPARC 10, 11 IBM AIX 6.1, 7.1
Included Paper Handling	550-Sheet Input 100-Sheet Multipurpose Feeder 550-Sheet Output Bin Integrated Duplex 550-Sheet Tray
Optional Paper Handling	550-Sheet Tray 2100-Sheet Tray
Paper Input Capacity, Standard	Up to 1200 pages 20 lb or 75 gsm bond
Paper Input Capacity, Maximum	Up to 2300 pages 20 lb or 75 gsm bond
Paper Output Capacity, Standard	Up to 550 pages 20 lb or 75 gsm bond
Paper Output Capacity, Maximum	Up to 1050 pages 20 lb or 75 gsm bond
Paper Weight Range Supported - Standard Tray (lb.)	16 - 47 lb.
Integrated Tray Card Stock Upper limit (grain short)	Cover - 176 gsm (65 lb) Index Bristol - 199 gsm (110 lb) Tag - 203 gsm (125 lb)
ADF	200-Sheet Automatic Document Feeder
ADF Paper Input Capacity	Up to 200 pages 20 lb or 75 gsm bond
ADF Paper Output Capacity	Up to 200 pages 20 lb or 75 gsm bond
Finishing Option	Yes
Number of Paper Inputs, Standard	3
Number of Paper Inputs, Maximum	6
Media Types Supported	Card Stock Dual Web Labels Envelopes Integrated Labels Paper Labels Plain Paper Transparencies Refer to the Card Stock & Label Guide.

Media Sizes Supported	10 Envelope 7 3/4 Envelope 9 Envelope A4 A5 B5 Envelope C5 Envelope DL Envelope Executive Folio JIS-B5 Legal Letter Statement Universal Oficio A6
Standard Ports	One Internal Card Slot USB 2.0 Specification Hi-Speed Certified (Type B) Gigabit Ethernet (10/100/1000) Front USB 2.0 Specification Hi-Speed Certified port (Type A) Rear USB 2.0 Specification Hi-Speed Certified Port (Type A)
Optional Local Ports	Internal RS-232C serial Internal 1284-B Bidirectional Parallel
Optional Network Ports	Marknet N8370 WiFi Option MarkNet N8230 Fiber Ethernet Print Server Marknet N8372 WiFi Option
Direct USB	Yes
Ethernet Network	Yes
Network Protocol Support	TCP/IP IPv4 AppleTalk™ TCP/IP IPv6 TCP UDP
Network Printing Methods	LPR/LPD Direct IP (Port 9100) Enhanced IP (Port 9400) FTP, TFTP ThinPrint .print integration Telnet IPP 1.0, 1.1, 2.0 (Internet Printing Protocol)
Network Management Protocols¹	HTTP HTTPs (SSL/TLS) SNMPv1, SNMPv2c SNMPv3 WINS IGMP BOOTP, RARP APIPA (AutoIP) DHCP ICMP DNS Bonjour DDNS mDNS ARP NTP Telnet Finger
Network Security	SNMPv3 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS IPSec
Printable Area	0.167 inches of the top, bottom, right and left edges (within)
Printer Languages (Standard)	PCL 5e Emulation PCL 6 Emulation Personal Printer Data Stream (PPDS) PostScript 3 Emulation Direct Image Microsoft XPS (XML Paper Specification) AirPrint™ PDF 1.7 emulation
Fonts and Symbol Sets	3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide 158 scalable PostScript fonts 2 PCL bitmap fonts 39 scalable PPDS fonts 5 PPDS bitmap fonts 84 scalable PCL fonts

OCR-A, OCR-B scalable PCL 5e fonts
For more information, refer to the Technical Reference.

Laser Cartridge Yields (up to)⁵
45,000-page Extra High Yield Cartridge

Imaging Unit Estimated Yield
Up to 150000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage⁴

Cartridge(s) Shipping with Product
11,000-page Starter Return Program Toner Cartridge

Replacement Cartridges:
Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details.

Packaged Size (in. - H x W x D)
53.7 x 30.0 x 32.7 in.

Packaged Weight (lb.)
222.66 lb.

Size (in. - H x W x D)
45.3 x 27.0 x 27.3 in.

Weight (lb.)
147.6 lb.

Noise Level, Idle
14 dBA

Noise Level (Print), Operating
56 dBA

Duplex Print Noise Level, Operating
55 dBA

Noise Level (Copy), Operating
59 dBA

Noise Level (Scan), Operating
57 dBA

ENERGY STAR
Yes

Average Power (Hibernate Mode)
0.2 watts

Average Power (Sleep Mode)
3.1 watts

Average Power (Ready Mode)
50 watts

Average Power (Printing)
850 watts

Average Power (Copying)
900 watts

Average Power (Scanning)
86 watts

ENERGY STAR Typical Electricity Consumption (TEC)
3.4 kilowatt-hours per week

Limited Warranty - See Statement of Limited Warranty
1-Year Onsite Repair, Next Business Day

Product Certifications
ENERGY STAR, Blue Angel RAL-UZ-171, ICES-003 Class A, BSMI Class A, VCCI Class A, US FDA/CDRH, UL 60950-1, FCC Class A, cUL CAN/CSA-C22.2 60950-1, NOM, MET-I, IEC 60825-1, CB EN/IEC 60950-1, CB EN/IEC 60825-1, CCD-035, CE DoC (EN 62301 Class A, EN 62311, CE EN/IEC 60950-1, CE EN/IEC 60825-1, EN 61000-3, EN 55022 Class A, EuP, EN 55024, UL), EFTA (CE), CISPR 22 Class A, KCC, CCC, CECP, CEL, A-tick DoC, C-tick CoC, UL-AR, KC mark, UL GS mark, ISO 532B, ECMA-370, TED, GOST-R, SII, TER, Bel GISS

Maximum Monthly Duty Cycle
Up to 350000 pages per month³

Recommended Monthly Page Volume
5000 - 100000 pages²

Specified Operating Environment
Humidity: 8 to 80% Relative Humidity
Temperature: 10 to 32°C (50 to 90°F)
Altitude: 0 - 2896 Meters (9,500 Feet)

License/Agreement Terms
Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details.

Country of Origin
China (PRC)

UNSPSC Code
43212110

Harmonized Tariff Code
8443.31.0000

¹This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (http://www.openssl.org/)
²Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

³Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.

⁴Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity.

⁵Average yield at approximately 5% print coverage per colour.

⁶Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.