

# Lexmark XM5365



<b>Part Number</b>	25B1200
<b>Print Technology</b>	Monochrome Laser
<b>Function</b>	Color Scanning Copying Faxing Network Scanning Printing
<b>Workgroup Size</b>	Large Workgroup
<b>Touch Screen Display</b>	Yes
<b>Display</b>	Lexmark e-Task 7-inch (17.8 cm) color touch screen
<b>Print Speed (Letter, Black)</b>	Up to 65 ppm <sup>6</sup>
<b>Print Speed (Letter, Black) Duplex</b>	Up to 39 spm <sup>6</sup>
<b>Time to First Page (Black)</b>	As fast as 4.2 seconds
<b>Duplex (2-sided) Printing</b>	Integrated Duplex
<b>Print Resolution, Black</b>	1200 Image Quality 1200 x 1200 dpi 2400 Image Quality 300 x 300 dpi 600 x 600 dpi
<b>Copy Speed (Letter, Black)</b>	Up to 65 cpm <sup>6</sup>
<b>Copy Speed (Letter, Black) Duplex</b>	Up to 41 spm <sup>6</sup>
<b>Time to First Copy (Black)</b>	As fast as 4.2 seconds
<b>Reduce / Enlarge Range</b>	25 - 400 <span> </span> %
<b>A4/Ltr Simplex Scan Speed (Black)</b>	Up to 72 / 75 sides per minute
<b>A4/Ltr Simplex Scan Speed (Color)</b>	Up to 72 / 75 sides per minute
<b>A4/Ltr Duplex Scan Speed (Black)</b>	Up to 144 / 150 sides per minute
<b>A4/Ltr Duplex Scan Speed (Color)</b>	Up to 144 / 150 sides per minute
<b>Scan Area, Maximum</b>	8.5 x 14.0 inches
<b>ADF Scan</b>	DADF (single pass Duplex)
<b>Scanner Type</b>	Flatbed scanner with ADF
<b>Scan Technology</b>	CCD
<b>Optical Scanning Resolution</b>	600 X 600 ppi (black) up to 600 X 600 ppi (color)
<b>Scan File Formats (Send as)</b>	JPEG, JPG PDF Secure PDF TIFF XPS Archival PDF (A-1a, A-1b) Searchable PDF (optional OCR with 1GB RAM and hard disk required) Highly compressed PDF (1GB RAM and hard disk required)
<b>Scan Destinations</b>	e-mail FTP USB Flash drive USB or Network connected computer Lexmark Document Solutions Suite (LDSS)
<b>Modem Speed</b>	33,600 BPS Max, V.34 Half Duplex Kbps
<b>Fax Transmission Speed</b>	< 3 seconds per page
<b>Processor</b>	Quad Core, 1200 MHz

<b>Memory, Standard</b>	2048 MB
<b>Memory, Maximum</b>	6144 MB
<b>Hard Disk</b>	Option available
<b>Apple Operating Systems Supported</b>	Apple OS X (10.6, 10.7, 10.8, 10.9, 10.10, 10.11, 10.12)
<b>Citrix MetaFrame</b>	Microsoft Windows 2000 Server running Terminal Services with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0. Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 4.0 Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 3.0, 4.0 Microsoft Windows Server 2012 with Citrix XenApp 6.0, 6.5
<b>Linux Operating Systems Supported</b>	Debian GNU/Linux 7.0, 8.0 SUSE Linux Enterprise Server 10, 11, 12 openSUSE Linux 13.2 Ubuntu 16.04 LTS Fedora 23, 24 Red Hat Enterprise Linux WS 6, 7 openSUSE Linux 42.3
<b>Microsoft Windows Operating Systems Supported</b>	Windows 7 Windows 7 x64 Windows 8 Windows 8 x64 Windows 8.1 Windows 8.1 x64 Windows 10
<b>Novell Operating Systems Supported</b>	Novell NetWare 6.5 Open Enterprise Server Novell NetWare 5.1(SP 6+), 6.0(SP 3+) with Novell Distributed Print Services (NDPS) Novell Open Enterprise Server on SUSE Linux Enterprise Server Novell Open Enterprise Server 2 on SUSE Linux Enterprise Server 10 SP4 Novell Open Enterprise Server 11 on SUSE Linux Enterprise Server 11 Novell Open Enterprise Server 2 SP2 on SuSE Linux Enterprise Server 10 SP3 3
<b>UNIX Operating Systems Supported</b>	Sun Solaris x86 10, 11 Sun Solaris SPARC 10, 11 IBM AIX 6.1, 7.1
<b>Included Paper Handling</b>	550-Sheet Input 100-Sheet Multipurpose Feeder 550-Sheet Output Bin Integrated Duplex
<b>Optional Paper Handling</b>	250-Sheet Tray 550-Sheet Tray 2100-Sheet Tray 250-Sheet Lockable Tray 550-Sheet Lockable Tray
<b>Paper Input Capacity, Standard</b>	Up to 650 pages 20 lb or 75 gsm bond
<b>Paper Input Capacity, Maximum</b>	Up to 3300 pages 20 lb or 75 gsm bond
<b>Paper Output Capacity, Standard</b>	Up to 550 pages 20 lb or 75 gsm bond
<b>Paper Output Capacity, Maximum</b>	Up to 550 pages 20 lb or 75 gsm bond
<b>Paper Weight Range Supported - Standard Tray (lb.)</b>	16 - 47 lb.
<b>Integrated Tray Card Stock Upper limit (grain short)</b>	Cover - 176 gsm (65 lb) Index Bristol - 199 gsm (110 lb) Tag - 203 gsm (125 lb)
<b>ADF</b>	200-Sheet Automatic Document Feeder
<b>ADF Paper Input Capacity</b>	Up to 200 pages 20 lb or 75 gsm bond
<b>ADF Paper Output Capacity</b>	Up to 200 pages 20 lb or 75 gsm bond
<b>Finishing Option</b>	No
<b>Number of Paper Inputs, Standard</b>	2
<b>Number of Paper Inputs, Maximum</b>	5
<b>Media Types Supported</b>	Card Stock Dual Web Labels Envelopes Integrated Labels Paper Labels Plain Paper Transparencies Refer to the Card Stock & Label Guide.

<b>Media Sizes Supported</b>	10 Envelope 7 3/4 Envelope 9 Envelope A4 A5 B5 Envelope C5 Envelope DL Envelope Executive Folio JIS-B5 Legal Letter Statement Universal Oficio A6
<b>Standard Ports</b>	One Internal Card Slot USB 2.0 Specification Hi-Speed Certified (Type B) Gigabit Ethernet (10/100/1000) Front USB 2.0 Specification Hi-Speed Certified port (Type A) Rear USB 2.0 Specification Hi-Speed Certified Port (Type A)
<b>Optional Local Ports</b>	Internal RS-232C serial Internal 1284-B Bidirectional Parallel
<b>Optional Network Ports</b>	Marknet N8370 WiFi Option MarkNet N8230 Fiber Ethernet Print Server Marknet N8372 WiFi Option
<b>Direct USB</b>	Yes
<b>Ethernet Network</b>	Yes
<b>Network Protocol Support</b>	TCP/IP IPv4 AppleTalk™ TCP/IP IPv6 TCP UDP
<b>Network Printing Methods</b>	LPR/LPD Direct IP (Port 9100) Enhanced IP (Port 9400) Secure IP (Port 96xx) FTP, TFTP ThinPrint .print integration IPP 1.0, 1.1, 2.0 (Internet Printing Protocol) Microsoft Web Services WSD Pull Printing
<b>Network Management Protocols1</b>	HTTP HTTPs (SSL/TLS) SNMPv1, SNMPv2c SNMPv3 WINS IGMP BOOTP, RARP APIPA (AutoIP) DHCP ICMP DNS Bonjour DDNS mDNS ARP NTP Telnet Finger
<b>Network Security</b>	SNMPv3 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS IPSec
<b>Printable Area</b>	0.167 inches of the top, bottom, right and left edges (within)
<b>Printer Languages (Standard)</b>	PCL 5e Emulation PCL 6 Emulation Personal Printer Data Stream (PPDS) PostScript 3 Emulation Direct Image Microsoft XPS (XML Paper Specification) AirPrint™ PDF 1.7 emulation
<b>Fonts and Symbol Sets</b>	3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide 158 scalable PostScript fonts 2 PCL bitmap fonts 39 scalable PPDS fonts

5 PPDS bitmap fonts 84 scalable PCL fonts OCR-A, OCR-B scalable PCL 5e fonts For more information, refer to the Technical Reference.	
<b>Laser Cartridge Yields (up to)<sup>5</sup></b> 45,000-page Extra High Yield Cartridge	
<b>Imaging Unit Estimated Yield</b> Up to 150000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage <sup>4</sup>	
<b>Cartridge(s) Shipping with Product</b>	11,000-page Starter Return Program Toner Cartridge
<b>Packaged Size (in. - H x W x D)</b>	40.2 x 27.6 x 28.9 in.
<b>Packaged Weight (lb.)</b>	129 lb.
<b>Size (in. - H x W x D)</b>	29.1 x 22.0 x 22.8 in.
<b>Weight (lb.)</b>	97.2 lb.
<b>Noise Level, Idle</b>	14 dBA
<b>Noise Level (Print), Operating</b>	57 dBA
<b>Duplex Print Noise Level, Operating</b>	56 dBA
<b>Noise Level (Copy), Operating</b>	60 dBA
<b>Noise Level (Scan), Operating</b>	56 dBA
<b>ENERGY STAR</b>	Yes
<b>Average Power (Hibernate Mode)</b>	0.2 watts
<b>Average Power (Sleep Mode)</b>	1.8 watts
<b>Average Power (Ready Mode)</b>	41.5 watts
<b>Average Power (Printing)</b>	800 watts
<b>Average Power (Copying)</b>	830 watts
<b>Average Power (Scanning)</b>	75 watts
<b>ENERGY STAR Typical Electricity Consumption (TEC)</b>	2.9 kilowatt-hours per week
<b>Limited Warranty - See Statement of Limited Warranty</b>	1-Year Onsite Repair, Next Business Day
<b>Product Certifications</b>	ENERGY STAR, ICES-003 Class A, BSMI Class A, VCCI Class A, US FDA/CDRH, UL 60950-1, FCC Class A, cUL CAN/CSA-C22.2 60950-1, NOM, MET-1, IEC 60825-1, CB EN/IEC 60950-1, CB EN/IEC 60825-1, CCD-035, CE DoC (EN 62301 Class A, EN 62311, CE EN/IEC 60950-1, CE EN/IEC 60825-1, EN 61000-3, EN 55022 Class A, EuP, EN 55024, UL), EFTA (CE), CISPR 22 Class A, KCC, CCC, CECP, CEL, A-tick DoC, C-tick CoC, UL-AR, KC mark, UL GS mark, ISO 532B, ECMA-370, TED, GOST-R, SII, TER, Bel GISS
<b>Maximum Monthly Duty Cycle</b>	Up to 300000 pages per month <sup>3</sup>
<b>Recommended Monthly Page Volume</b>	5000 - 75000 pages <sup>2</sup>
<b>Specified Operating Environment</b>	Humidity: 8 to 80% Relative Humidity Temperature: 10 to 32°C (50 to 90°F) Altitude: 0 - 2896 Meters (9,500 Feet)
<b>License/Agreement Terms</b>	Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details.
<b>Country of Origin</b>	China (PRC)
<b>UNSPSC Code</b>	43212110
<b>Harmonized Tariff Code</b>	8443.31.0000
<sup>1</sup> This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (http://www.openssl.org/)	
<sup>2</sup> "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.	
<sup>3</sup> "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.	
<sup>4</sup> Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity.	
<sup>5</sup> Average yield at approximately 5% print coverage per colour.	
<sup>6</sup> Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.	